

Suits single and double sized Rolling doors up to 15m<sup>2</sup>

Soft start & stop to reduce door stress Automatic courtesy light





SPECIFICATIONS		SPECIFICATION EXPLAINED
Peak Pulling Force	500N	The motor's peak pulling force should suit the door type to provide optimal performance with minimal noise.
Motor Type	DC	Our custom designed DC motor delivers smooth, quiet and reliable operation.
Max. Recommended Door Size	15m²	Each opener is specifically designed to efficiently operate doors up to a specific size.
Soft Start / Soft Stop	Yes	Increases and decreases the speed of operation to reduce stress on the door and reduce noise.
Low Standby Power	Yes	When the opener is not in operation, you can rest assured that it is not excessively draining power.
Service Indicator	Yes	The clever logics inside our Controll-A-Door® openers alert you when a service is due to maximise the life of your opener.
Courtesy Light	Yes – LED	The courtesy light illuminates when the door is opened improving visibility and safety.
Remote Controls	x 3	Our Premium Tri-Tran+™ remote controls provide superior security and excellent operating range whilst virtually eliminating interference from other wireless devices.
Warranty	2 Years / 5,000 Cycle*	We offer a 2 year / 5,000 cycle manufacturer's warranty backed by a nationwide team of garage door and opener service professionals.

B&D has offices servicing all states. For more details on this product or other ranges phone **13 62 63** or visit **www.bnd.com.au** 

\*Full details of manufacturer's warranty can be found at www.bnd.com.au



THERE'S SO MUCH MORE BEHIND A B&D DOOR

YOUR **B&D REPRESENTATIVE** IS:

International Customers call +61 2 9722 5555 fax +61 2 9771 6385 or email bndint@bnd.com.au